



Multi-Touch ProPanel

INTERACTIVE FLAT PANEL

65"

DESCRIPTION

The Multi-Touch NTRON ProPanel combines multi-touch functionality, reliable operation and an interactive whiteboard software that makes it the best solution for classrooms and meeting rooms at an affordable cost.



MULTI-TOUCH INTERACTIVE FLAT PANEL

Multi-user interactivity with 10-touch points supporting collaboration, coordination and parallel problem solving.



SMART DESIGN

Supports multiple gestures in windows, reliable 18/7 operation, easy to use and maintain. Android Sytem, WiFi, optional Win 10 with Intel i3/i5/i7 OPS.



PLUG and PLAY

Connect the NTRON ProPanel to the power socket and start working instantly without the need to install any additional software or driver . It also supports connecting to external computer or laptop.



FHD RESOLUTION

Brilliant Full HD resolution across a wide viewing angle.



INTERACTIVE WHITEBOARD SOFTWARE

Powerful software with easy-to-use tools and functions which creates engaging lessons and interactive meetings.

| PRODUCT SPECIFICATIONS

Display

Diagonal Size	65"	Glass Surface	AR/AG
Aspect Ratio	16:9	Display Colors	1.07 Billion
Resolution	1920 x 1080	Response Time	< 5ms
Screen Type	LG Panel - DLED	Viewing Angle	178°/178°
Contrast Ratio	5000 : 1	Refresh Rate	120Hz
Brightness	450cd/m2	Service Life	> 50000 Hrs

Interactivity

Touch Points	10-Touch
Touch Technology	Infrared
Touch Accuracy	+/-2 mm
Touch Resolution	32,768 x 32,768 px
Response Time	8ms
Glass Type	Anti-glare 4mm Tempered Glass

Dimensions

Product Dimensions	1515 x 935 x 102 mm
Packing Dimensions	1675 x 1110 x 255 mm
Active Area Diagonal	65 inches
Net/Gross Weight	50KG / 64KG

Power and Drivers

Power Supply	220V AC 50/60Hz
Power Consumption	<= 160W
Driver Mode	Plug & Play

Connectivity and Audio

Input	USB2.0 x 2, VGA x 1, AV x 2, Mic x 1, HDMI x 2, SD x 1, SPDIF x 1
Output	VGA x 1, AV x 1, Audio x 1
Speakers	Front-facing stereo speakers 10W x 2
Network	Gigabit RJ45 x 1, WiFi I/O RS-232 x 1

Environmental

Operating Temperature	0°C to 40°C (32°F to 104°F)
Operating Humidity	20% to 80% non-condensing humidity

Packed Contents

Remote Control x 1, Power Cable x 1, Pen x 2, Wall Mount x 1

Warranty

Standard Warranty 2 Years Warranty - RTB